

Handmade for quality



LabHEAT[®] metal-cased heating mantles series KM-ME

for operating temperatures up to 450°C

- for flasks, round bottom with volume up to 20 l
- with built-in controller
allows a continuous adjustment of power outlet
- flexible glass yarn heating element
an even heat transfer and a gentle treatment of the glassware
- plastic-coated metal housing
characterised by a chemical-resistant metal housing providing excellent stability
- high quality design
made by hand work
- thermally insulated and earthed
- predrilled threaded hole on rear allows to fix the clamp KM-SK (accessories)
- with built-in heating zone switch
- with residual current detection (RCD)
- **CE**
our heating mantles perform the requirements based on the european harmonized standards



Technical specification

KM-ME

Nominal voltage	230 V AC
Nominal power output	see ordering details
Heating zones	see ordering details
Safety class	I
System of protection	Casing IP 43, heating surface IP 00
Heating element temperature	max. 450°C
Power supply cable	1,5 m with schuko-plug (earthed) and RCD switch

Heating-zone selection

Switch position	Min	Max
1 heating zone		
Power	1/2	1/1
2 heating zones		
Power	1/2	1/1

Ordering details

Volume ml / l	Flask Ø mm	Power W	Heating zones	Dimensions Ø x H mm	Part.-No.
50	51	55	1	175 x 180	92000050
100	64	100	1	175 x 180	92000100
250	85	150	2	175 x 180	92000250
500	105	200	2	220 x 190	92000500
1	131	300	2	220 x 190	92001000
2	166	500	2	300 x 220	92002000
3	185	600	2	300 x 220	92003000
4	207	750	2	360 x 240	92004000
5	223	860	2	360 x 240	92005000
6	236	1000	2	360 x 240	92006000
10	279	1400	2	370 x 250	92010000
20	345	2000	2	440 x 270	92020000

We also manufacture special heating mantles with other specifications - available on request

Accessories

Support clamp type KM-SK	Part.-No. 97000001
to fix support rods with diameter up to Ø 13 mm	

We supply a full range of controllers and temperature regulators.

SAF Wärmetechnik GmbH
Weinheimer Str. 2a
D-69509 Mörlenbach

Tel. + 49 (0) 6209 797 96-0
Fax + 49 (0) 6209 797 96-29

E-Mail: info@saf-gmbh.de
Internet: www.saf-gmbh.de