

Handmade for quality



## **LabHEAT<sup>®</sup> metal-cased heating mantles** **series KM-MNB**

for operating temperatures up to 450°C

- for beakers, low form
- flexible glass yarn heating element  
*an even heat transfer and a gentle treatment of the glassware*
- plastic-coated metal housing  
*characterised by a chemical-resistant metal housing providing excellent stability*
- high quality design  
*made by hand work*
- thermally insulated and earthed
- predrilled threaded hole on rear allows to fix the clamp KM-SK (accessories)
- with built-in heating zone switch
- with residual current detection (RCD)
- **CE**  
*our heating mantles perform the requirements based on the european harmonized standards*





## Technical specification

## KM-MNB

Nominal voltage	230 V AC
Nominal power output	see ordering details
Heating zones	see ordering details
Safety class	I
System of protection	casing IP 43, heating surface IP 00
Heating element temperature	max. 450°C
Power supply cable	1,5 m with schuko-plug (earthed) and RCD switch

## Heating-zone selection

Switch position	Min	Max
		
2 heating zones		
Power	1/2	1/1

## Ordering details

Volume ml / l	Beaker* Ø x H mm	Power W	Heating zones	Dimensions Ø x H mm	Part.-No.
400	80 x 100	200	2	175 x 180	94000001
600	90 x 116	260	2	175 x 180	94000002
1	105 x 145	400	2	220 x 190	94000003
2	132 x 186	600	2	220 x 190	94000004
3	152 x 210	800	2	300 x 220	94000005

\*heated hight approx. 2/3 of beaker

We also manufacture special heating mantles with other specifications - available on request

## Accessories

Support clamp type KM-SK	Part.-No. 97000001
to fix support rods with diameter up to Ø 13 mm	

We supply a full range of controllers and temperature regulators.

**SAF Wärmetechnik GmbH**  
**Weinheimer Str. 2a**  
**D-69509 Mörlenbach**

**Tel. + 49 (0) 6209 797 96-0**  
**Fax + 49 (0) 6209 797 96-29**

**E-Mail: [info@saf-gmbh.de](mailto:info@saf-gmbh.de)**  
**Internet: [www.saf-gmbh.de](http://www.saf-gmbh.de)**