

## SciPette StepMate Stepper









## SciPette

Based on the principle of positive displacement, StepMate Stepper is designed for trouble-free and reliable dispensing of liquids, especially for high viscosity, high density and high vapor pressure. The 48-step dispensing allows for enhanced accuracy and usability.

- Light and ergonomic solution provides easy usability
- Single-handed operation
- Volume range from 10µL to 5mL
- Up to 48 dispensing steps
- Maintenance free
- Equipped with durable tip insertion lever
- Fits seven sizes of disposable polypropylene syringes from 0.5mL to 50mL

## How to select dispensing volume

Find the required dispensing volume in the table Use the adjusting wheel to set the required volume Select and insert a suitable tip Follow the maximum dispensing steps

			1
		store /	
	and		
()			
Pro la			

Tip Volume	e							
	Dispensing Volume							
Tips Sel	1	2	3	4	5			
0.50ml	10µI	20µI	30µl	40µI	50µ			
1.25ml	25µ1	50µl	75µl	100µI	125µ			
2.50ml	50µl	100µľ	150µl	200µl	250µ			
5.00ml	100µl	200µl	300µI	400µl	500µ			
12,50ml	250µl	500µl	750µI	1000µl	1250µ			
25.00ml	500µI	1000µl	1500µi	2000µ1	2500µ			
50.00ml	1000µ1	2000µl	3000µl	4000µl	5000µ			
Steps	48	23	15	11	8			

Steps

SciQuip Ltd Newtown Wem Shrewsbury Shropshire SY4 5NU, UK Tel: +44 (0)1939 234222 Fax: +44 (0)1939 234221 Email: info@sciquip.co.uk www.sciquip.co.uk





## SciPette

+++

Dial setting		1	2	3	4	5	Specifications		
Number of steps		48	23	15	11	8	Note: The first and last dispensing liquid should be discarded for precision.		
Cat. No.	Syringe volume (mL)	Sample volume (μL)					Α%	Р%	Description
SP3051	0.50	10	20	30	40	50	± 0.8	≤ 0.7	0.5mL, piston PE-HD, cylinder PP, 1 packing, 5 pcs/packing
SP3052	1.25	25	50	75	100	125	± 0.8	≤ 0.5	1.25mL, piston PE-HD, cylinder PP, 1 packing, 5 pcs/packing
SP3053	2.50	50	100	150	200	250	± 0.8	≤ 0.4	2.5mL, piston PE-HD, cylinder PP, 1 packing, 5 pcs/packing
SP3054	5.00	100	200	300	400	500	± 0.4	≤ 0.3	5mL, piston PE-HD, cylinder PP, 1 packing, 5 pcs/packing
SP3055	12.50	250	500	750	1000	1250	± 0.3	≤ 0.3	12.5ml, piston PE-HD, cylinder PP, 1 packing, 5 pcs/packing
SP3056	25.00	500	1000	1500	2000	2500	± 0.2	≤ 0.3	25mL, piston PE-HD, cylinder PP, 1 packing, 2pcs/packing with 1 pc adapter
SP3057	50.00	1000	2000	3000	4000	5000	± 0.2	≤ 0.2	50mL, piston PE-HD, cylinder PP, 1 packing, 2pcs/packing with 1 pc adapter

SciPette stepper tips are particularly suitable for dispensing of fluids with high viscosity, high vapor pressure etc.

Tips are made from high-quality materials (Cylinder: PP, Piston: PE-HD) without soft lubricants or other additives.

SciQuip Ltd Newtown Wem Shrewsbury Shropshire SY4 5NU, UK Tel: +44 (0)1939 234222 Fax: +44 (0)1939 234221 Email: info@sciquip.co.uk www.sciquip.co.uk