Chest freezer XLT C300

- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable
- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 45001 Certified

Specifications

Technical

Gross volume	296 litres
Net Volume	284 litres
Temp. range	-40°C to -60°C
Temp. probes	1/PT 1000
Compressor	Embraco
Baskets (incl./optional)	3/9
Refrigerant	Nature R
Noise level	55 dB
Power consumption 24/h	5,5 kWh
Power consumption	2.007 kWh / year
Voltage	230V
Frequency	50 Hz

Features

Audible and visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup	NO
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø12 mm
Connection for remote alarm	Optional

Material

Inner	Precoated white steel
Outer	Galvanized pre-coated steel

Outer dimensions

Height (with castors)	885 mm
Width	1260 mm
Depth (incl. condenser)	630 mm
Depth (incl. condenser & handle)	680 mm
Net weight	71 kg

Inner dimensions

Height	635/385 mm
Width	1100/890 mm
Depth	440 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

XLT C300

Product no.	N112003

Storage capacity

Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	6	3	18	N311200
	11	18	198	N311220
			= 216	
75 mm	4	3	12	N311300
	8	18	144	N311320
			= 156	
100 mm	3	3	9	N311400
	5	18	90	N311420
			= 99	