



Platform scale in heavy version with EC type approval [M], now also up to [Max] 600 kg

Features

- **Tough industry standard** suitable for use in harsh industrial applications
- **1 Platform:** weighing plate stainless steel, painted steel base, silicone-coated aluminium load cell, protection against dust and water splashes IP65, Platform can also be delivered as component without the display device, for details see KERN KFP V20

- **Benchtop stand incl. wall mount** for display device as standard

Technical data

- Large backlit LCD display, digit height 52 mm
- Weighing plate dimensions, stainless steel W×D×H



- A 300×240×110 mm
- B 400×300×128 mm
- C 500×400×130 mm, see larger picture
- D 650×500×142 mm
- E 800×600×200 mm

- Cable length of display device approx. 3 m
- Permissible ambient temperature - 10 °C/40 °C

Accessories

- **Protective working cover**, can be re-ordered, scope of delivery: 5 items, KERN KFB-A02S05
- **Rechargeable battery pack internal**, operating time up to 35 h, without backlight, charging time approx. 12 h, must be ordered at purchase, KERN KFB-A01
- **Stand** to elevate display device, for models with weighing plate size A, B: height of stand approx. 330 mm, KERN IFB-A01
C–E: 2 height of stand approx. 600 mm, KERN IFB-A02
A–D: height of stand approx. 800 mm, KERN BFS-A07
- Further details, plenty of further accessories and suitable printers see *Accessories*

STANDARD



OPTION



FACTORY



Model	Weighing range [Max] kg	Read-out [d] g	Verification value [e] g	Minimal load [Min] g	Net weight approx. kg	Weighing plate	Options			
							Verification		DAkkS Calibr. Certificate	
							M KERN		DKD KERN	
KERN										
IFB 6K-4	6	0,2	-	-	6	A	-		963-128	
IFB 10K-4	15	0,5	-	-	6	A	-		963-128	
IFB 10K-4L	15	0,5	-	-	10	B	-		963-128	
IFB 30K-3	30	1	-	-	10	B	-		963-128	
IFB 60K-3	60	2	-	-	10	B	-		963-129	
IFB 60K-3L	60	2	-	-	13	C	-		963-129	
IFB 100K-3	150	5	-	-	14	C	-		963-129	
IFB 100K-3L	150	5	-	-	22	D	-		963-129	
IFB 300K-2	300	10	-	-	20	D	-		963-129	
IFB 600K-2	600	20	-	-	46	E	-		963-130	
Dual-range balance switches automatically to the next largest weighing range [Max] and readout [d]										
IFB 6K1DM	3 6	1 2	1 2	20 40	6	A	965-228		963-128	
IFB 15K2DM	6 15	2 5	2 5	40 100	6	A	965-228		963-128	
IFB 15K2DLM	6 15	2 5	2 5	40 100	10	B	965-228		963-128	
IFB 30K5DM	15 30	5 10	5 10	100 200	11	B	965-228		963-128	
IFB 60K10DM	30 60	10 20	10 20	40 100	11	B	965-229		963-129	
IFB 60K10DLM	30 60	10 20	10 20	200 400	13	C	965-229		963-129	
IFB 150K20DM	60 150	20 50	20 50	400 1000	14	C	965-229		963-129	
IFB 150K20DLM	60 150	20 50	20 50	400 1000	20	D	965-229		963-129	
IFB 300K50DM	150 300	50 100	50 100	1000 2000	22	D	965-229		963-129	
IFB 600K-1M	300 600	100 200	100 200	2000 4000	46	E	965-230		963-130	

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible.

Verification at the factory, we need to know the full address of the location of use.

KERN Pictograms:



Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven).



Piece counting: Reference quantities selectable. Display can be switched from piece to weight.



Rechargeable battery pack: Rechargeable set.



Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.



Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).



Universal mains adapter: with universal input and optional input socket adapters for
A) EU, GB
B) EU, GB, CH, USA
C) EU, GB, CH, USA, AUS



Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.



Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.



Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available.



Alibi memory: Electronic archiving of weighing results, complying with the 2014/31/EU standard.



Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition.



Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.



Data interface RS-232: To connect the balance to a printer, PC or network.



Weighing principle: Strain gauge
Electrical resistor on an elastic deforming body.



RS-485 data interface: To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.



Totalising level A: The weights of similar items can be added together and the total can be printed out.



Weighing principle: Tuning fork
A resonating body is electromagnetically excited, causing it to oscillate.



USB data interface: To connect the balance to a printer, PC or other peripherals.



Percentage determination: Determining the deviation in % from the target value (100 %).



Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings.



Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals.



Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.



Weighing principle: Single cell technology
Advanced version of the force compensation principle with the highest level of precision.



WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals.



Weighing with tolerance range: Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning.



Verification possible:
The time required for verification is specified in the pictogram.



Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.



Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value.



DAKkS calibration possible (DKD): The time required for DAKkS calibration is shown in days in the pictogram.



Interface for second balance: For direct connection of a second balance.



Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.



Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.



Network interface: For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.



ATEX explosion protection: Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device.



Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.



Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module.



Stainless steel: The balance is protected against corrosion.



Warranty: The warranty period is shown in the pictogram.



GLP/ISO log: The balance displays the weight, date and time, regardless of a printer connection.



Suspended weighing: Load support with hook on the underside of the balance.



GLP/ISO log: With weight, date and time. Only with KERN printers.



Battery operation: Ready for battery operation. The battery type is specified for each device.

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg - 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer: